## **Ø22/25 Emergency Switches (S2ER Series)**

1.		Contact block		LED block			
Appearance	Model	A contact	B contact	AC/DC voltage	AC voltage		
	S2ER-E1RA(M)	1	_				
	S2ER-E1R2A(M)	2					
	S2ER-E1R3A(M)	3					
	S2ER-E1RB(M)		1				
	S2ER-E1R2B(M)		2		_		
	S2ER-E1R3B(M)		3				
	S2ER-E1RAB(M)	1	1				
	S2ER-E1R2AB(M)	2	1				
	S2ER-E1RA2B(M)	1	2				
S2ER_E1P□	contact block.  **The control unit, contact (control unit: bold letters,	<ul> <li>**The M in the model name indicates modular type contact block. Models without M are singular contact block.</li> <li>**The control unit, contact blocks, LED blocks are sold separately. (control unit: bold letters, contact block: regular letters)</li> </ul>					
OZEN-E INC.	• Dimensions	<b>-&gt;</b> +	Panel thickness: Max. 6	<u>Smm</u>	(unit: mm)		
	30.4	29.4	B		A B type 48.5 27.0 ype 46.5 25.0		
	※For panel cut-out dimensions, please refer to page A-82.						
Appearance	Model			LED block			
	COED FORA(M)	_		AC/DC voltage	AC voltage		
	` ,		_				
		_					
	` ,	_		_	_		
			+				
The state of the s	<ul> <li>**The M in the model name indicates modular type contact block. Models without M are singular contact block.</li> <li>**The control unit, contact blocks, LED blocks are sold separately.</li> </ul>						
S2ER-E2R□	Dimensions		<u> </u>				
		ī.	Panel thickness: Max. 6m	m	(unit: mm)		
	1	→   <del>  ·</del>		<u></u>			
		S2ER-E1R2A(M) S2ER-E1R3A(M) S2ER-E1RB(M) S2ER-E1R3B(M) S2ER-E1RAB(M) S2ER-E2RA(M) S2ER-E2RA(M) S2ER-E2RAB(M)	S2ER-E1R2A(M)   2   S2ER-E1R3A(M)   3   S2ER-E1R3A(M)   3   S2ER-E1R2B(M)	S2ER-E1R2A(M)   2	S2ER-E1R2A(M)   2		

XFor panel cut-out dimensions, please refer to page A0-78.

A-76 Autonics

Ø16 Ø22/25

□30

Round
Square
Rectangular

Round
Square
Rectangular

Pilot Lights

Accessories

Buzzers

T	A 10 10 20 10 10 20 20 20 20 20 20 20 20 20 20 20 20 20	Model	Contact block	<b>(</b>	LED block	LED block		
Гуре	Appearance	Model	A contact	B contact	AC/DC voltage	AC voltage		
D40		S2ER-E3RA(M)	1	_				
(short head)		S2ER-E3RA(M)	2	_				
		S2ER-E3R3A(M)	3	_				
		S2ER-E3RB(M)	_	_ 1				
		S2ER-E3R2B(M)	_	2		_		
		<b>S2ER-E3R</b> 3B(M)	_	3				
		S2ER-E3RAB(M)	1	1				
	(m=m)	S2ER-E3R2AB(M)	2	1				
		S2ER-E3RA2B(M)	1	2				
		※The M in the model name	indicates modular tvr		dels without M are sind	gular contact, blo		
		**The M in the model name  **The control unit, contact (control unit: bold letters,	blocks, LED blocks	pe contact block. Mod are sold separately		gular contact blo		
	S2ER-E3R□	*The control unit, contact	blocks, LED blocks	pe contact block. Mod are sold separately		gular contact blo		
	S2ER-E3R□	**The control unit, contact (control unit: bold letters,	blocks, LED blocks contact block: regu	pe contact block. Mod are sold separately	<i>i.</i>	gular contact blo		
	S2ER-E3R□	<ul><li>*The control unit, contact (control unit: bold letters,</li><li>Dimensions</li></ul>	blocks, LED blocks contact block: regu	pe contact block. Mod are sold separately lar letters)	<i>i.</i>			
	S2ER-E3R□	<ul><li>*The control unit, contact (control unit: bold letters,</li><li>Dimensions</li></ul>	blocks, LED blocks contact block: regu	pe contact block. Mod are sold separately lar letters)	7.			

※For panel cut-out dimensions, please refer to page A-82.

Type	Appearance	Model	Contact block		LED block	
Туре	Арреагапсе	Wodel	A contact	B contact	AC/DC voltage	AC voltage
D40		S2ER-E4RAD(M)	1	_	1	_
(short head/		S2ER-E4R2AD(M)	2	_	1	_
illuminated)		S2ER-E4R3A(M)	3	_	_	_
		S2ER-E4RBD(M)	_	1	1	_
		S2ER-E4R2BD(M)	_	2	1	_
		S2ER-E4R3B(M)	_	3	_	_
		S2ER-E4RABL(M)	1	1	_	1
	R. RISSEL	S2ER-E4R2AB(M)	2	1	_	_
		S2ER-E4RA2B(M)	1	2	_	_
		**The M in the model name indic **The control unit, contact bloc (control unit: bold letters, con	ks, LED blocks are	sold separately.		
	S2ER-E4R□	• Dimensions	23.7	anel thickness: Max. 6mm	Singular to	

Autonics A-77

%For panel cut-out dimensions, please refer to page A-82.

Time	Appearance	Model	Contact block		LED block	
Туре			A contact	B contact	AC/DC voltage	AC voltage
D60		S2ER-E5RA(M)	1	_		
(short head)		S2ER-E5R2A(M)	2	_		
neau)		S2ER-E5R3A(M)	3	_		
		S2ER-E5RB(M)	_	1		
		S2ER-E5R2B(M)	_	2	]_	_
	E 73	S2ER-E5R3B(M)	_	3		
		S2ER-E5RAB(M)	1	1		
	My Trees of	S2ER-E5R2AB(M)	2	1		
	ten en	S2ER-E5RA2B(M)	1	2		
	S2ER-E5R□	*The control unit, contact bloc (control unit: bold letters, control unit: bold letter	act block: regular	Panel thickness: Max	Singular to	

A-78 Autonics

## **Ø22/25 Panel Cut-out Dimensions**

(unit: mm)

Туре		A	В	Panel Cut-out Dimensions	
Round/Square Push Button Switches (S2PR/S2PRS Series)			33	55	
Round Selector Switches	Short lever	dans	33	55	
(S2SR/S2SRN Series)	Long lever	dame	55	55	<mounting hole:="" ø25=""></mounting>
Round Key Selector Switches (S2KR Series)		33	55	Min. A <sup>±0.5</sup> Ø25.5	
Double Push Button Switches (S2TR Series)		33	60		
Mushroom-head Push Button Switches (S2BR Series)		33	55	<mounting hole:="" ø22=""> R1 3 Ø22.5</mounting>	
D30			33	55	20
Emergency Switches (S2ER Series)	D40		55	55	
	D60		80	80	
Pilot Lights (L2RR Series)		33	55		

A-82 Autonics